Scientific Instruments GmbH

Roemerstr. 67 | 82205 Gilching/Germany | Phone: +49 8105 77940 | E-mail: info@si-gmbh.de | Web: www.si-gmbh.de

Analytical Instrumentation


Surf the New Wave in Portable Fiber Optic Spectrometry

BLUE-Wave Miniature Fiber Optic Spectrometers for UV-VIS-NIR & OEM

The StellarNet BLUE-Wave Spectrometers are fiber optic coupled instruments with a wide selection of models for measurements in 190-1150nm wavelength ranges using a 16-bit digitizer via high speed USB-2.

Each unit contains a USB-2 interface with a snap shot memory to provide instantaneous spectral image from the highly sensitive CCD or CMOS detectors with 2048 elements. Various models provide a choice of grating range and slit resolutions.

A single strand fiber optic cable or probe assembly delivers input via standard SMA 905 fiber optic connector with a choice of cable The spectrograph optics exceptionally robust in a vibration tolerant modular design, with no moving parts. The detachable spectrograph assembly and



LED spectra of red, green, blue, white



BLUE-Wave 16-bit USB2 Spectrometers

control electronics are protected inside a rugged metal enclosure, suitable for portable, process, and lab applications. Several units may be daisy-chained using a powered USB2 hub allowing simple configurations for dual and multi-beam applications in chemistry, spectro-radiometry, PORTA-LIBS, and industrial process controls.

The SpectraWiz software is included to accurately measure light emission intensity for LED, Laser, plasma, solar, xenon, and so on. Measurement applications include SpectroRadiometry (NIST traceable intensities, LED xy chromaticty), Spectro-Colorimetry (CIELAB L* a* b*), Chemistry concentration/reaction time analysis, UVabc monitors, Spectral-ID of elemental plasma emissions, and more.

Specifications		BLUE-Wave Spectrometers			
Dynamic range:	2000:1 with 6 decades	Dimensions:	1x3x5 inch = $25x75x125$ mm		
Optical resolution:	see model table - to 0.2nm	Weight:	14 ounces		
Detector type:	CCD or CMOS	Power consumption:	< 100 mA via USB port		
Detector range:	200-1150nm (UV - add \$)	Interface:	USB-2 or USB-2 Hub		
Pixel size:	14 x 200um or 7 x 200um	Detector Integration:	1ms to 65s		
Diffraction Gratings:	Holographic & Ruled	Slit size options:	14, 25, 50, 100, 200um		
Grating g/mm:	300, 600, 1200, 1800, 2400	Stray light:	<.1% at 435nm;<.05% at 600nm		
Spectrograph:	f/4, SymX-Czerny-Turner	Fiber optic input:	SMA905 0.22na single fiber		
Order sorting filters:	Integrated & High Pass	Operating systems:	Windows		
Signal to noise:	1000:1	Software included:	SpectraWiz program & apps		
Digitizer:	16-bit	Also free programs for:	LabView,Excel+VBA,Delphi		






BLUE-Wave Miniature Fiber Optic Spectrometers for UV-VIS-NIR & OEM


Additional measurement applications include emission wavelength monitoring /characterization of tunable lasers or LED's and other sources such as elemental emissions from plasma & Laser Induced Breakdown Spectroscopy. Also Bragg grating technology enables optical sensing of many


parameters including temperature and pressure. Thin film thickness measurements can be made using sample specular reflectance. The small size and weight makes the BLUE-Wave spectrometers just perfect for portable and OEM applications.

BLUE-Wave Spectrometer Configurations			2048 pixel CCD detector		Predicted Slit Resolving Resolutions		
Model	Wavelength	Grating	Slit-200	Slit-100	Slit-50	Slit-25	Slit-14
	Range in nm	g/mm	nm res.	nm res.	nm res.	nm res.	nm res.
UV	200-600	1200	3.0	1.6	0.8	0.50	0.40
UV2	200-400	2400	1.5	0.8	0.4	0.25	0.20
UV3	220-350	3600	1.0	0.5	0.25	0.16	0.13
UVIS	300-1100	600	6.0	3.2	1.6	1.00	0.80
VIS	350-1150	600	6.0	3.2	1.6	1.00	0.80
VIS2	380-780	1200	3.0	1.6	0.8	0.50	0.40
NIR	500-1150	600	6.0	3.2	1.6	1.00	0.80
NIR2	600-1000	1200	3.0	1.6	0.8	0.50	0.40
NIR2b	785-1150	1200	3.0	1.6	0.8	0.50	0.40
NIR3	550-840	1800	2.2	1.2	0.6	0.35	0.28
NIR3b	680-935	1800	2.2	1.2	0.6	0.35	0.28
NIR4	500-700	2400	1.5	0.8	0.4	0.25	0.20
NIR4b	600-800	2400	1.5	0.8	0.4	0.25	0.20
UVN	250-1100	600	6.0	3.2	1.6	1.00	0.80
UVNb	200-1050	600	6.0	3.2	1.6	1.00	0.80



UVN spectra of mercury+argon gas





UV-VIS spectra of a thin film



